



Main Particulars

Length	33.3 m
Moulded Beam	6.5 m
Depth	3.3 m
Gross Tonnage	168 T
Net Tonnage	60 T
Deck Area	75 m ²
Davit	NA

Accommodation

Crew	6
Charterers Accommodation	12
Crew Transfer Seats	Nil
Air Conditioning	Yes

Life Saving Equipment

Lifebuoys	6
Lifejackets	22
Life Rafts	2 x 20 pax
EPIRB	McMurdo
SART	McMurdo – S4 Rescue SART

Additional Equipment

Ballistically protected bridge to STANAG Level 1.
 Mess room Port and Stbd sides ballistically protected to STANAG Level 1.
 Electronic Fuel Monitoring (EFMS).

Performance

Cruise Speed	12 Knots
Maximum Speed	23 Knots
Fuel consumption @8kn	1.0 m ³ /24h
Fuel consumption @12kn	2.5 m ³ /24h
Fuel consumption @20kn	10 m ³ /24h
Range	5000 NM
Endurance	17 Days
(Max. 35 days task depending)	

Classification

Class	Bureau Veritas
Type	Fast Support Intervention
Built	2012
Ship Builder	Damen, Singapore
Flag	Palau
Port of Registry	Malakal Harbor
Official Number	SR2378
IMO Number	9664744
Call Sign	T8A3413

Capacities

Fuel Capacity	47 m ³
Potable Water Capacity	18 m ³
Deck Cargo	20 T

Fire Safety Equipment

Safety Equipment as per SOLAS, Flag and Class Society requirement.

Machinery

Main Engines	3 x C32 TTA = 2685 kw
Generators	2 X Caterpillar C4.4

Navigation Equipment

Radar	JRC JMA 5212-4/6
	S - band JRC / JMA 5312
Searchlight	2 x 240V 1000W Seematz
Auto Pilot	Alpha Sea Pilot MFC
Echo sounder	Alphatron - Alpha depth
Magnetic compass	Ritchie – HB-74
Satellite navigation(GPS)	JRC JRL 7500
	JRC JRL 21/31
Electronic Compass	Maretron - Fluxgate
Depth Sounder	AlphaDepth
AIS	JRC JHS-182

Communication Eqpt.

SSB radio	ICOM78
VHF radio	ICOM78
MF/HF	2 x Sailor 6222
VHF DSC	JRC NCR-333
Navtex	KVHV7
Email/Sat phone	Inmarsat C
Tracking device	Inmarsat C
Air band VHF	Dittel FSG 90
VHF GMDSS hand held	Sailor SP 3520